## **Product Information**



## PRODUCT FICHE

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

Heat pump combination heater		Outdoor Indoor	ERLA14DAW1 EBBX16DF9W
Indoor unit sound power (*)		Tank [dB(A)]	EKHWS150D3V3
later heating	Declared load profile Energy efficiency class	-	A
pace Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
vverage climate (Design temperature = -10°C) Vater heating	Water heating energy efficiency (n. 1.)	[%]	87
	Water heating energy efficiency (n <sub>Wh</sub> )		
Space Heating	Annual energy consumption	[kWh] [kW]	1,184
	Prated (declared heating capacity) @ -10°C		
	Seasonal space heating efficiency ( $\eta$ ( $\eta_S$ )	[%]	128
	Annual energy consumption	[kWh]	6,962
ff peak operation function integrated in Heat pump older climate (Design temperature = -22°C)		Y/N	false
later heating	Water heating energy efficiency (η <sub>W</sub> h)	[%]	69
	Annual electricity consumption (AEC)	[kWh]	1,491
Space Heating	Prated (declared heating capacity) @ -22°C	[kW]	11
		[%]	118
	Seasonal space heating efficiency ( $\eta$ ( $\eta_S$ )	[/0]	110
	Annual energy consumption	[kWh]	8,974
Warmer climate (Design temperature = 2°C) Water heating	Water heating energy efficiency /nl-	[%]	100
	Water heating energy efficiency (n <sub>W</sub> h)		1 022
Space Heating	Annual electricity consumption (AEC)	[kWh] [kW]	1,023
	Prated (declared heating capacity) @ 2°C		
	Seasonal space heating efficiency ( $\eta_S$ )	[%]	171
	Annual energy consumption	[kWh]	3,717
Ecodesign technical data Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N V/N	No No
	Low-temperature heat pump Equipped with a supplementary heater	Y/N Y/N	No
	Heat pump combination heater	Y/N	No
ir to water unit	Rated airflow (outdoor)	[m <sup>3</sup> /h]	4,220
rine/water to water unit	Rated water/brine flow (outdoor H/E)	[m <sup>3</sup> /h]	
Other	Capacity control	-	Inverter
	Poff (Power consumption Off mode)	[kW]	0.023
	P <sub>†O</sub> (Power consumption Thermostat off mode)	[kW]	0.023
		[kW]	0.023
	P <sub>Sb</sub> (Power consumption Standby mode)		
	PCK (Power crankcase heater model)	[kW]	0.000
	Q <sub>elec</sub> (Daily electricity consumption)	[kWh]	5.61
		[kWh]	
	Q <sub>fuel</sub> (Daily fuel consumption)	[KWII]	
Part load conditions space heating average climate A) condition (-7°C)		[kW]	8.5
	Pdh (declared heating capacity)	[KVV]	6.5
	COP <sub>C</sub> (declared COP)	-	1.80
	Cdh (degradation coefficient)	-	1.0
B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.2
			3.28
	COPd (declared COP)		
C) condition (7°C)	Cdh (degradation coefficient)		1.0 4.4
	Pdh (declared heating capacity)	[KVV]	4.4
	COP <sub>d</sub> (declared COP)	-	4.88
	Cdh (degradation coefficient)	-	1.0
(D) (D) condition (12°C)	Pdh (declared heating capacity)	[kW]	5.3
	COP <sub>d</sub> (declared COP)	-	6.58
			10
(E) Tol (temperature operating limit)	Cdh (degradation coefficient)  Tol (temperature operating limit)	- [°C]	1.0 -10
	Pdh (declared heating capacity)	[kW]	7.0
			1.76
	COPd (declared COP)		
	WTOL (Heating water Operation Limit)	[°C]	-5
F) Tbivalent temperature	<sup>T</sup> blv	[°C]	
	Pdh (declared heating capacity)	[kW]	8.9
		-	1.87
	COPd (declared COP)		
apacity of the back-up heater integrated in the unit	P <sub>Sup</sub> back-up heater (@Tdesignh: -10°C)	[kW]	9.0
upplementary capacity at P_design	P <sub>Sup</sub> (@Tdesignh: -10°C)	[kW]	4.0

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'

(\*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.