Product Information



PRODUCT FICHE

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

Heat pump combination heater		Outdoor	ERLA16DAW1 EBBX16DF6V
iont parily communation months		Tank	EBBX16DF6V EKHWS150D3V3
ndoor unit sound power (*)		[dB(A)]	
utdoor unit sound power (*)		[dB(A)]	
ater heating	Declared load profile Energy efficiency class	<u>-</u>	L A
pace Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
verage climate (Design temperature = -10°C)		[%]	87
Vater heating	Water heating energy efficiency (n _{Wh})	[70]	67
The state of the s	Annual energy consumption	[kWh]	1,184
pace Heating	Prated (declared heating capacity) @ -10°C	[kW]	12
	Seasonal space heating efficiency ($\eta(\eta_S)$	[%]	131
	Annual energy consumption	[kWh]	7,392
ff peak operation function integrated in Heat pump	Amidal energy consumption	Y/N	false
older climate (Design temperature = -22°C)		ra/3	laa.
Vater heating	Water heating energy efficiency (η _W ₁)	[%]	69
	Annual electricity consumption (AEC)	[kWh]	1,491
Space Heating	Prated (declared heating capacity) @ -22°C	[kW]	12
	Space and enace heating officiency (n (n -)	[%]	121
	Seasonal space heating efficiency (η (η_S)		0.540
armer climate (Design temperature = 2°C)	Annual energy consumption	[kWh]	9,510
Water heating	Water heating energy efficiency (n _W h)	[%]	100
		[kWh]	1,023
Space Heating	Annual electricity consumption (AEC)	[kW]	12.1
	Prated (declared heating capacity) @ 2°C		
	Seasonal space heating efficiency (η_S)	[%]	172
	Annual energy consumption	[kWh]	3,690
codesign technical data Product description	A in the state of head assume	V/N	Vac
	Air-to-water heat pump Water-to-water heat pump	Y/N Y/N	Yes No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump Equipped with a supplementary heater	Y/N Y/N	No No
	Heat pump combination heater	Y/N	No
ir to water unit	Rated airflow (outdoor)	[m3 _{/h]}	5,100
rine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control	-	Inverter
	POff (Power consumption Off mode)	[kW]	0.023
	-	[kW]	0.023
	P _{to} (Power consumption Thermostat off mode)		
	P _{Sb} (Power consumption Standby mode)	[kW]	0.023
	POLZ (Power crankcase heater model)	[kW]	0.000
	PCK (Power crankcase heater model)		
	Qelec (Daily electricity consumption)	[kWh]	5.61
	Qfuel (Daily fuel consumption)	[kWh]	
	-iuei ()	<u> </u>	
Part load conditions space heating average climate (A) condition (-7°C)	D :: (declared heating conseits)	[kW]	9.4
	Pdh (declared heating capacity)		0.1
	COP _d (declared COP)	-	1.95
	Cdh (degradation coefficient)	-	1.0
B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.9
			3.27
	COP _C (declared COP)		0.27
	Cdh (degradation coefficient)		1.0
C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.4
	COP _C (declared COP)	-	4.93
	Cdh (degradation coefficient)		1.0
(D) (D) condition (12°C)	Pdh (declared heating capacity)	 [kW]	5.3
	· UII (accounted floating surprising)		
	COP _d (declared COP)		6.60
	Cdh (degradation coefficient)	-	1.0
	Tol (temperature operating limit)	[sC]	-10 6.0
	Pdh (declared heating capacity)	[kW]	J0
	COP _d (declared COP)	-	1.50
	WTOL (Heating water Operation Limit)	[°C]	55
(F) Tbivalent temperature	Tblv	[°C]	-5
		na-n	10.1
	Pdh (declared heating capacity)	[kW]	10.1
	COP _d (declared COP)	-	2.13
	`	0.340	0.0
apacity of the back-up heater integrated in the unit	P _{SUP} back-up heater (@Tdesignh: -10°C)	[kW]	6.0
		[kW]	6.1

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu'

(*) Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.